

SPEC SHEET

Corner Cabinet



Specifications

Top is 16 gauge 304 stainless steel #4 finish. Front and back edges are turned down 102° and turned back 90° eliminating the gap between the top and the base of the cabinet. The ends are turned down 90° flush with cabinet base, this eliminates any open space between G.A. Systems cabinets. The top is secured to the base with 4 stainless steel flush head screws. One 3/4" diameter pin is welded at one end of the top. The pin has two 5/16" diameter holes. The lower hole is used to join adjacent G.A. Systems cabinets.

Body of cabinet is fabricated of 1" square 18 gauge stainless steel and cold rolled tubing to form the top and bottom frames. Each is welded to 1-1/2" square 18 gauge stainless steel corner posts. Each corner post is capped. All joints are welded with all exposed welds being ground and polished. 20 gauge galvanized body panels are welded to tubing super structure.

Exterior front, back and one end are trimmed with 22 gauge stainless steel #4 finish trim to accept laminated color panels. Laminate is applied to 1/8" board for additional strength.

Bottom is fully enclosed. There is a 3-3/4" clearance from the bottom of the cabinet to the floor. Plate type 3" swivel non-marking casters with brakes. Cabinet heights are ADA compliant.


Dimensions

ITEM	MODEL	WIDTH	WIDTH	HEIGHT
C0456	SP30	30-3/8"	30-3/8"	34"
C0542	SP36	36-3/8"	36-3/8"	34"
C1115	ESP30	30-3/8"	30-3/8"	31-1/2"
C1078	ESP36	36-3/8"	36-3/8"	31-1/2"

PROJECT:	
ITEM #:	
MODEL:	

Standard Features

- \square Locking pin, one at each end
- ☐ Plate type 3" swivel non-marking casters with brakes



Rev 04/2019