



G.A. SYSTEMS, Inc.

SPECIALIZING IN CAFETERIA SERVING LINES

SPEC SHEET

Half Round End Cabinet



Specifications

Top is 16 gauge 304 stainless steel #4 finish. The end is turned down 90° flush with cabinet base, this eliminates any open space between G.A. Systems cabinets. The top is secured to the base with silicone and two stainless steel flush head screws. One 3/4" diameter pin is welded at one end of the top. The pin has two 5/16" diameter holes. The lower hole is used to join adjacent G.A. Systems cabinets.

Body of cabinet is fabricated of 1" square 18 gauge stainless steel and cold rolled tubing to form the top and bottom frames. Each is welded to 1-1/2" square 18 gauge stainless steel corner posts. Each corner post is capped. All joints are welded with all exposed welds being ground and polished. 20 gauge galvanized body panels are welded to tubing super structure.

Laminate is applied using an industrial contact cement.

Bottom is fully enclosed. There is a 3-3/4" clearance from the bottom of the cabinet to the floor. Plate type 3" swivel non-marking casters with brakes. Cabinet heights are ADA compliant.

Dimensions

ITEM	MODEL	LENGTH	WIDTH	HEIGHT
C0595	RD END	23-1/2"	46-1/2"	34"

Note: Attach this cabinet to other G.A. Systems cabinet or secure to wall for stability.

PROJECT: _____

ITEM #: _____

MODEL: _____

Standard Features

- ☐ Locking pin, 1

Options




- ☐ Toe kick
- ☐ Solid Surface Top (in lieu of stainless steel top)



Half Round End Cabinet shown with D4830 Merchandising Cabinet, sliding doors and toe kick accessories



Half Round End Cabinet shown with Solid Surface Material Option and toe kick accessories



Rev 07/2019